

Standard configuration

Part Information No	Description	Quantity
1	OTDR host	1
2	AC/DC power adapter	1
3	Cortical handle	1
4	U disk (containing client simulation analysis software)	1
5	Touch pen	1
6	Data line	1
7	OTDR SC Transfer interface	1
8	OPM SC Transfer interface	1
9	User's Manual	1
10	Test Report	1
11	Warranty card and Certificate	1
12	Clean cotton swab	1
13	Special backpack for instrument (containing suspenders)	1



Front



Top



Angle

Optical Time-domain Reflectometer OTDR(FS-18R)



FOSTEC

HEAD OFFICE

(15655)Fostec Bldg., 40, MTV 20-ro 12beon-gil, Danwon-gu, Ansan-si, Gyeonggi-do, Korea

Tel : +82-31-318-9350 Fax : +82-31-318-9352

E-mail : sales@fostec.co.kr Website : www.fostec.co.kr

FEATURES

- 5.8 inch color LCD with touch screen
- Built-in stabilization light source 1310 / 1550nm
- Built-in optical power meter, VFL
- Independent and convenient one-touch automatic test function
- Two wavelength synchronization test functions
- Two waveform view functions
- Low battery alarm function



The image displays two views of the FOSTEC Optical Time Domain Reflectometer (OTDR). The top view shows the front panel, which features a color LCD screen displaying a menu with options like LS, VFL, OPM, and OTDR. The bottom view shows the back panel, which includes various ports and connectors.